

Push-In Fitting QS-G1/8-6-I - Festo 186107

Item no. FES-186107

Manufacturer Festo

EAN 4052568014636

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

TECHNICAL DATA

HS-Code	74122000
Pneumatischer Anschluss	G1/8
Weight	0.0082 kg
Werkstoff	Messing



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

size	Standard
Nominal width [mm]	4,2
Seal type on stud	gasket
installation position	arbitrary
Packing size	10
Construction set up	Push-pull principle
Operating pressure complete temperature range [bar]	-0.95 to 6
Temperature depending operating pressure [bar]	-0.95 to 14
Maritime classification	see Certificate
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:] Water according to manufacturer declaration at www.festo.com

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Information about operating and control medium	Oiled operation possible
Corrosion resistant class KBK	1 - low corrosion stress
ambient temperature [°C]	-10 to 80
Product weight [g]	8,3
Pneumatic connection 1	Male thread G1/8
Pneumatic connection 2	For hose exterior diameter 6 mm
Sleeve colour	 blue
Material information	RoHs compliant
Housing material	brass nickel-plated
Sleeve material	POM
Tube seal, hose seal material	NBR
Hose clamping segment material	High-alloyed stainless steels
Nominal tightening torque [Nm]	7,00
Tolerance to nominal tightening torque	± 20 %