

Push-In Sleeve QSH-6 - Festo 153252

Item no. FES-153252

Manufacturer Festo

EAN 4052568033293

Festo pneumatic component for industrial automation and compressed-air applications in proven quality.

TECHNICAL DATA

HS-Code **39174000**

Weight **0.0008 kg**

Werkstoff **PBT**



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic component for industrial automation and compressed-air applications in proven quality. The key technical data of this genuine Festo article are listed below.

size	Standard
Nominal width [mm]	4,0
installation position	arbitrary
Packing size	10
Construction set up	Push-pull principle
Operating pressure complete temperature range [bar]	-0.95 to 6
Temperature depending operating pressure [bar]	-0.95 to 14
Maritime classification	see Certificate
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-] Water according to manufacturer declaration at www.festo.com

Information about operating and control medium	Oiled operation possible
Corrosion resistant class KBK	1 - low corrosion stress
ambient temperature [°C]	-10 to 80
Product weight [g]	0,5
Pneumatic connection 1	Plug sleeve QS-6
Pneumatic connection 2	Plug sleeve QS-6
Sleeve colour	 blue
Material information	RoHs compliant
Housing material	PBT