

Push-In L-Connector QSL-4H - Festo 153056

Item no.	FES-153056	Manufacturer	Festo
Manufacturer no.	QSL-4H	EAN	4052568031510

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

TECHNICAL DATA

Article authenticity	Original product
Condition of article	New
HS-Code	39174000
Weight	0.003 kg
Werkstoff	PBT



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

size	Standard
Nominal width [mm]	2,0
installation position	arbitrary
Packing size	10
Construction set up	Push-pull principle
Operating pressure complete temperature range [bar]	-0.95 to 6
Temperature depending operating pressure [bar]	-0.95 to 14
Maritime classification	see Certificate
Operating medium	Compressed air to ISO 8573-1:2010 [7::-] Water according to manufacturer declaration at www.festo.com
Information about operating and control medium	Oiled operation possible

Corrosion resistant class KBK	1 - low corrosion stress
ambient temperature [°C]	-10 to 80
Product weight [g]	2,7
Pneumatic connection 1	Plug sleeve QS-4
Pneumatic connection 2	For hose exterior diameter 4 mm
Sleeve colour	 blue
Material information	RoHs compliant
Housing material	PBT
Sleeve material	POM
Tube seal, hose seal material	NBR
Hose clamping segment material	High-alloyed stainless steels