

Push-In L-Fitting QSL-V0-1/2-10 - Festo 160520

Item no. FES-160520

Manufacturer Festo

EAN 4052568035693

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

TECHNICAL DATA

Baugröße BG	Standard
Corrosion resistance class CRC	2 - moderate corrosion stress
Design	Push-pull principle
HS-Code	74122000
Material	PBT
Medium	Compressed air, water
Nennweite DN [mm]	8,3
Pneumatic connection	R1/2
Series	QSL
Temperature (max.)	60
Weight	0.06 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

size	Standard
Nominal width [mm]	8,3
Fire inspection, material	UL94 V-0 (Housing) UL94 V-0 (sleeve)
Seal type on stud	coating
Construction set up	Push-pull principle
Operating pressure complete temperature range [bar]	-0.95 to 10
Maritime classification	see Certificate
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-] Water according to manufacturer declaration at www.festo.com
Information about operating and control medium	Oiled operation possible
Corrosion resistant class KBK	2 - moderate corrosion stress

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com
esd.equipment

Page 1/2

ambient temperature [°C]	0 to 60
Product weight [g]	59,0
Pneumatic connection 1	R1/2
Pneumatic connection 2	For hose exterior diameter 10 mm
Sleeve colour	 black
Stud material	Nickel-plated brass
Material information	RoHs compliant
Housing material	PBT reinforced
Hose clamping segment material	High-alloyed stainless steels brass