

Multiple Distributor QSLV4-G1/4-8 - Festo 186247

Item no. FES-186247

Manufacturer Festo

EAN 4052568040499

Festo pneumatic component for industrial automation and compressed-air applications in proven quality.

TECHNICAL DATA

Baugröße BG	Standard
Corrosion resistance class CRC	1 - low corrosion stress
Design	Push-pull principle
HS-Code	74122000
Material	PBT
Medium	Compressed air, water
Mounting position	arbitrary
Nennweite DN [mm]	4,1
Pneumatic connection	G1/4
Series	QSLV4
Temperature (max.)	80
Weight	0.055 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic component for industrial automation and compressed-air applications in proven quality. The key technical data of this genuine Festo article are listed below.

size	Standard
Nominal width [mm]	4,1
Seal type on stud	gasket
installation position	arbitrary
Construction set up	Push-pull principle
Packing size	1
Operating pressure complete temperature range [bar]	-0.95 to 6
Temperature depending operating pressure [bar]	-0.95 to 14
Maritime classification	see Certificate

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-] Water according to manufacturer declaration at www.festo.com
Information about operating and control medium	Oiled operation possible
Corrosion resistant class KBK	1 - low corrosion stress
ambient temperature [°C]	-10 to 80
Product weight [g]	54,0
Number of outlets	4
Number of supply lines	1
Pneumatic connection 1	Male thread G1/4
Pneumatic connection 2	For hose exterior diameter 8 mm
Sleeve colour	 blue
Material information	RoHs compliant
Housing material	PBT
Sleeve material	POM
Tube seal, hose seal material	NBR
Hose clamping segment material	High-alloyed stainless steels
Nominal tightening torque [Nm]	9,0
Tolerance to nominal tightening torque	± 20 %