

# Push-In T-Fitting QSMTL-G1/8-6 - Festo 186275

<b>Item no.</b>	FES-186275	<b>Manufacturer</b>	Festo
<b>Manufacturer no.</b>	QSMTL-G1/8-6	<b>EAN</b>	4052568040734

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

## TECHNICAL DATA

Article authenticity	<b>Original product</b>
Condition of article	<b>New</b>
HS-Code	<b>74122000</b>
Pneumatischer Anschluss	<b>G1/8</b>
Weight	<b>0.012 kg</b>
Werkstoff	<b>PBT</b>



## STANDARDS & COMPLIANCE

**ISO 8573-1:2010**

## DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

size	Mini
Nominal width [mm]	3,3
Seal type on stud	gasket
installation position	arbitrary
Packing size	10
Construction set up	Push-pull principle
Operating pressure complete temperature range [bar]	-0.95 to 6
Temperature depending operating pressure [bar]	-0.95 to 14
Maritime classification	see Certificate
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-]

Information about operating and control medium	Oiled operation possible
Corrosion resistant class KBK	1 - low corrosion stress
ambient temperature [°C]	-10 to 80
Product weight [g]	12,0
Pneumatic connection 1	Male thread G1/8
Pneumatic connection 2	For hose exterior diameter 6 mm
Sleeve colour	<span class="farbe" style="background-color:#009FE3"></span> blue
Material information	RoHs compliant
Housing material	PBT
Sleeve material	POM
Tube seal, hose seal material	NBR
Hose clamping segment material	High-alloyed stainless steels
Nominal tightening torque [Nm]	7,00
Tolerance to nominal tightening torque	± 20 %
Number of outlets	2
Number of supply lines	1