

Rotary Push-In Fittin QSR-1/8-4 - Festo 153401

Item no. FES-153401

Manufacturer Festo

EAN 4052568034412

Festo rotary actuator for defined swivel motion and positioning in automation.

TECHNICAL DATA

HS-Code	74122000
Pneumatischer Anschluss	R1/8
Weight	0.015 kg
Werkstoff	PBT



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo rotary actuator for defined swivel motion and positioning in automation. The key technical data of this genuine Festo article are listed below.

size	Standard
Nominal width [mm]	2,1
installation position	arbitrary
Packing size	1
Construction set up	Push-pull principle
Operating pressure complete temperature range [bar]	-0.95 to 6
Temperature depending operating pressure [bar]	-0.95 to 14
Maritime classification	see Certificate
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-]
Information about operating and control medium	Oiled operation possible

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Corrosion resistant class KBK	1 - low corrosion stress
ambient temperature [°C]	0 to 60
Product weight [g]	14,0
Pneumatic connection 1	Male thread R1/8
Pneumatic connection 2	For hose exterior diameter 4 mm
Sleeve colour	 blue
Material information	RoHs compliant
Housing material	PBT
Sleeve material	POM
Tube seal, hose seal material	NBR
Hose clamping segment material	High-alloyed stainless steels
Seal type on stud	coating
Max. tightening torque [Nm]	7,0
Max. speed [1/min]	500
Max. radial torque [Nm]	0,006