

# Push-In T-Fitting QST-3/8-16 - Festo 164959

<b>Item no.</b>	<b>FES-164959</b>	<b>Manufacturer</b>	<b>Festo</b>
<b>Manufacturer no.</b>	<b>QST-3/8-16</b>	<b>EAN</b>	<b>4052568073534</b>

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

## TECHNICAL DATA

Article authenticity	<b>Original product</b>
Condition of article	<b>New</b>
HS-Code	<b>74122000</b>
Pneumatischer Anschluss	<b>R3/8</b>
Weight	<b>0.089 kg</b>
Werkstoff	<b>PBT</b>



## STANDARDS & COMPLIANCE

**ISO 8573-1:2010**

## DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

size	Standard
Nominal width [mm]	11,0
Seal type on stud	coating
installation position	arbitrary
Packing size	1
Construction set up	Push-pull principle
Operating pressure complete temperature range [bar]	-0.95 to 6
Temperature depending operating pressure [bar]	-0.95 to 14
Maritime classification	see Certificate

Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-] Water according to manufacturer declaration at <a href="http://www.festo.com">www.festo.com</a>
Information about operating and control medium	Oiled operation possible
Corrosion resistant class KBK	1 - low corrosion stress
ambient temperature [°C]	-10 to 80
Product weight [g]	89,0
Pneumatic connection 1	Male thread R3/8
Pneumatic connection 2	For hose exterior diameter 16 mm
Sleeve colour	<span class="farbe" style="background-color:#009FE3"></span> blue
Material information	RoHs compliant
Housing material	PBT
Sleeve material	POM
Tube seal, hose seal material	NBR
Hose clamping segment material	High-alloyed stainless steels
Number of outlets	2
Number of supply lines	1