

Silencer U-1/8-B - Festo 6841

Item no. FES-6841

Manufacturer Festo

EAN 4052568001407

Festo pneumatic component for industrial automation and compressed-air applications in proven quality.

TECHNICAL DATA

Corrosion resistance class
CRC **1 - low corrosion stress**

HS-Code **84879090**

Medium **Druckluft**

Mounting position **arbitrary**

Pneumatischer Anschluss **G1/8**

Temperature (max.) **70**

Weight **0.008 kg**

Werkstoff **Aluminium**



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic component for industrial automation and compressed-air applications in proven quality. The key technical data of this genuine Festo article are listed below.

installation position	arbitrary
Operating pressure complete temperature range [bar]	0 to 10
Flow against atmosphere [l/min]	1.340
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-]
Information about operating and control medium	Oiled operation possible
Corrosion resistant class KBK	1 - low corrosion stress
Sound level [dB(A)]	74,0
ambient temperature [°C]	-10 to 70
Product weight [g]	8,0
Pneumatic connection	G1/8
Dampening insert material	PE

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Stud material	Aluminium
Material information	Copper and PTFE-free RoHs compliant
Housing material	Aluminium