

Service Unit FRC-1/2-D-7-DI-MAXI-A - Festo 192426

Item no. FES-192426

Manufacturer Festo

EAN 4052568151621

Festo air-preparation unit for clean, regulated compressed air that protects downstream components.

TECHNICAL DATA

Betriebsdruck max [bar]	12.000000
HS-Code	84811005
Pneumatischer Anschluss	G1/2
Weight	3 kg
Werkstoff	Zink-Druckguss



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo air-preparation unit for clean, regulated compressed air that protects downstream components. The key technical data of this genuine Festo article are listed below.

size	Maxi
Model series	D
Actuation fuse	Rotary button with stopper
installation position	vertical $\pm 5^\circ$
Condensate drain	Fully automatic
Construction set up	Filter regulator with pressure gauge Proportional standard oil mist lubricator
Max. condensate amount [ml]	43
Filter porosity [μm]	40
Clamp protection	Metal protection basket
pressure display	with pressure gauge
Operating pressure [bar]	2 to 12

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Pressure regulation range [bar]	0.5 to 12
Max. pressure hysteresis [bar]	0,4
Normal nominal flow [l/min]	4.500
Maritime classification	see Certificate
Operating medium	Compressed air to ISO 8573-1:2010 [-:-:-]
Medium temperature [°C]	-10 to 60
ambient temperature [°C]	-10 to 60
Product weight [g]	2.600
Fastening type	pipe installation
Pneumatic connection 1	G1/2
Pneumatic connection 2	G1/2
Housing material	Zinc pressure cast
Clamps material	PC