

Service Unit FRC-1/2-D-7-O-MIDI - Festo 192635

Item no. FES-192635

Manufacturer Festo

EAN 4052568152765

Festo air-preparation unit for clean, regulated compressed air that protects downstream components.

TECHNICAL DATA

Baugröße BG	Midi
Betriebsdruck max [bar]	16.000000
Design	Filter regulator without pressure gauge, Proportional standard oil mist lubricator
Durchfluss [l/min]	2800
Filterfeinheit [µm]	40
HS-Code	84811005
Kondensatablass	manual rotary
Material	Die-cast zinc
Medium	Compressed air, neutral gases
Mounting position	vertical ± 5°
Pneumatic connection	G1/2
Regelbereich max. [bar]	7
Series	FRC
Temperature (max.)	60
Weight	1.8 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo air-preparation unit for clean, regulated compressed air that protects downstream components. The key technical data of this genuine Festo article are listed below.

size	Midi
Model series	D
Actuation fuse	Rotary button with stopper
installation position	vertical ± 5°
Condensate drain	Manually rotating
Construction set up	Filter regulator without pressure gauge Proportional standard oil mist lubricator
Max. condensate amount [ml]	43
Filter porosity [µm]	40

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Clamp protection	Metal protection basket
pressure display	G1/4 prepared
Operating pressure [bar]	1 to 16
Pressure regulation range [bar]	0.5 to 7
Max. pressure hysteresis [bar]	0,2
Normal nominal flow [l/min]	2.800
Maritime classification	see Certificate
Operating medium	Inert gases Compressed air to ISO 8573-1:2010 [-:9:-]
Information about operating and control medium	Oiled operation possible (required in further operations)
Air purity class at the output	Inert gases Compressed air to ISO 8573-1:2010 [7:8:-]
Medium temperature [°C]	-10 to 60
ambient temperature [°C]	-10 to 60
Product weight [g]	1.440
Fastening type	pipe installation With Accessories
Pneumatic connection 1	G1/2
Pneumatic connection 2	G1/2
Material information	RoHs compliant
Housing material	Zinc pressure cast
Clamps material	PC