

Service Unit FRC-1/8-D-MINI-KA-A - Festo 185792

Item no. FES-185792

Manufacturer Festo

EAN 4052568145507

Festo air-preparation unit for clean, regulated compressed air that protects downstream components.

TECHNICAL DATA

Baugröße BG	Mini
Betriebsdruck max [bar]	12.000000
Corrosion resistance class CRC	2 - moderate corrosion stress
Design	Branching module, Filter regulator with pressure gauge, Proportional standard oil mist lubricator
Durchfluss [l/min]	650
Filterfeinheit [µm]	40
HS-Code	84811005
Kondensatablass	fully automatic
Material	Die-cast zinc
Medium	Compressed air, neutral gases
Mounting position	vertical ± 5°
Pneumatic connection	G1/8
Regelbereich max. [bar]	12
Series	FRC
Temperature (max.)	60
Weight	1.3 kg



STANDARDS & COMPLIANCE

ISO8573-1:2010 ISO 8573-1:2010

DESCRIPTION

Festo air-preparation unit for clean, regulated compressed air that protects downstream components. The key technical data of this genuine Festo article are listed below.

size	Mini
Model series	D
Actuation fuse	Rotary button with stopper
installation position	vertical ± 5°
Filter porosity [µm]	40
Condensate drain	Fully automatic
Construction set up	Branching module Filter regulator with pressure gauge Proportional standard oil mist lubricator

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Max. condensate amount [ml]	22
Clamp protection	Metal protection basket
pressure display	with pressure gauge
Operating pressure [bar]	2 to 12
Pressure regulation range [bar]	0.5 to 12
Max. pressure hysteresis [bar]	0,15
Normal nominal flow [l/min]	650
Maritime classification	see Certificate
Operating medium	Compressed air to ISO8573-1:2010 [-:-:-] Inert gases
Corrosion resistant class KBK	2 - moderate corrosion stress
Air purity class at the output	Compressed air to ISO 8573-1:2010 [7:4:-] Inert gases
Medium temperature [°C]	-10 to 60
ambient temperature [°C]	-10 to 60
Product weight [g]	1.000
Fastening type	pipe installation With Accessories Selectively:
Pneumatic connection 1	G1/8
Pneumatic connection 2	G1/8
Housing material	Zinc pressure cast
Clamps material	PC