

Service Unit FRC-3/8-D-O-MIDI-A - Festo 162749

Item no. FES-162749

Manufacturer Festo

EAN 4052568132613

Festo air-preparation unit for clean, regulated compressed air that protects downstream components.

TECHNICAL DATA

Betriebsdruck max [bar]	12.000000
HS-Code	84811005
Pneumatischer Anschluss	G3/4
Weight	1.9 kg
Werkstoff	Zink-Druckguss



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo air-preparation unit for clean, regulated compressed air that protects downstream components. The key technical data of this genuine Festo article are listed below.

size	Midi
Model series	D
Actuation fuse	Rotary button with stopper
installation position	vertical $\pm 5^\circ$
Condensate drain	Fully automatic
Construction set up	Filter regulator with pressure gauge Proportional standard oil mist lubricator
Max. condensate amount [ml]	43
Filter porosity [μm]	40
Clamp protection	Metal protection basket
pressure display	G1/4 prepared
Operating pressure [bar]	2 to 12

Pressure regulation range [bar]	0.5 to 12
Max. pressure hysteresis [bar]	0,2
Normal nominal flow [l/min]	2.600
Maritime classification	see Certificate
Operating medium	Inert gases Compressed air to ISO 8573-1:2010 [7:9:-]
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	2 - moderate corrosion stress
Air purity class at the output	Inert gases Compressed air to ISO 8573-1:2010 [7:8:-]
Medium temperature [°C]	-10 to 60
ambient temperature [°C]	-10 to 60
Product weight [g]	1.350
Fastening type	pipe installation With Accessories
Pneumatic connection 1	G3/4
Pneumatic connection 2	G3/4
Material information	RoHs compliant
Housing material	Zinc pressure cast
Clamps material	PC