

Service Unit FRC-M5-D-7-O-5M-MICRO - Festo 527862

Item no. FES-527862

Manufacturer Festo

EAN 4052568162962

Festo air-preparation unit for clean, regulated compressed air that protects downstream components.

TECHNICAL DATA

Betriebsdruck max [bar]	10.000000
HS-Code	84811005
Pneumatischer Anschluss	M5
Weight	0.103 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo air-preparation unit for clean, regulated compressed air that protects downstream components. The key technical data of this genuine Festo article are listed below.

size	Micro
Model series	D
Actuation fuse	Rotary button with stopper
installation position	vertical $\pm 5^\circ$
Condensate drain	Manually rotating
Construction set up	Filter regulator without pressure gauge Proportional standard oil mist lubricator
Max. condensate amount [ml]	3
Filter porosity [μm]	5
pressure display	M5 prepared
Operating pressure [bar]	1 to 10
Pressure regulation range [bar]	0.5 to 7

Max. pressure hysteresis [bar]	0,3
Normal nominal flow [l/min]	80
Operating medium	Compressed air to ISO 8573-1:2010 [-:-:-]
Medium temperature [°C]	-10 to 60
ambient temperature [°C]	-10 to 60
Product weight [g]	103
Fastening type	pipe installation With Accessories
Pneumatic connection 1	M5
Pneumatic connection 2	M5
Housing material	Aluminium wrought alloy
Clamps material	PC