

Filter LF-3/4-D-MAXI-A - Festo 159618

Item no. FES-159618

Manufacturer Festo

EAN 4052568126742

Festo air-preparation unit for clean, regulated compressed air that protects downstream components.

TECHNICAL DATA

Betriebsdruck max [bar]	12.000000
HS-Code	84213925
Pneumatischer Anschluss	G3/4
Weight	1.5 kg
Werkstoff	Zink-Druckguss



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo air-preparation unit for clean, regulated compressed air that protects downstream components. The key technical data of this genuine Festo article are listed below.

size	Maxi
Model series	D
installation position	vertical $\pm 5^\circ$
Filter porosity [μm]	40
Condensate drain	Fully automatic
Construction set up	Sintered filter with centrifugal separator
Max. condensate amount [ml]	80
Clamp protection	Metal protection basket
Operating pressure [bar]	2 to 12
Normal nominal flow [l/min]	5.000
Maritime classification	see Certificate

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Operating medium	Inert gases Compressed air to ISO 8573-1:2010 [7:9:-]
Corrosion resistant class KBK	2 - moderate corrosion stress
Bearing temperature [°C]	-10 to 60
Air purity class at the output	Compressed air to ISO 8573-1:2010 [7:8:4] Inert gases
Medium temperature [°C]	5 to 60
ambient temperature [°C]	5 to 60
Product weight [g]	1.340
Fastening type	pipe installation With Accessories
Pneumatic connection 1	G3/4
Pneumatic connection 2	G3/4
Material information	RoHs compliant
Filter material	PE
Housing material	Zinc pressure cast
Clamps material	PC