

Filter LF-D-MIDI - Festo 192552

Item no. FES-192552

Manufacturer Festo

EAN 4052568079505

Festo air-preparation unit for clean, regulated compressed air that protects downstream components.

TECHNICAL DATA

Betriebsdruck max [bar]	16.000000
HS-Code	84213925
Weight	0.65 kg
Werkstoff	Zink-Druckguss



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo air-preparation unit for clean, regulated compressed air that protects downstream components. The key technical data of this genuine Festo article are listed below.

size	Midi
Model series	D
installation position	vertical $\pm 5^\circ$
Filter porosity [μm]	40
Condensate drain	Manually rotating
Construction set up	Sintered filter with centrifugal separator
Max. condensate amount [ml]	43
Clamp protection	Metal protection basket
Operating pressure [bar]	0 to 16
Operating medium	Inert gases Compressed air to ISO 8573-1:2010 [-:9:-]
Corrosion resistant class KBK	2 - moderate corrosion stress

Bearing temperature [°C]	-10 to 60
Air purity class at the output	Compressed air to ISO 8573-1:2010 [7:8:4] Inert gases
Medium temperature [°C]	-10 to 60
ambient temperature [°C]	-10 to 60
Product weight [g]	700
Fastening type	pipe installation With Accessories
Pneumatic connection 1	Connection plate
Pneumatic connection 2	Connection plate
Material information	RoHs compliant
Filter material	PE
Housing material	Zinc pressure cast
Clamps material	PC