

Filter LF-QS4-D-5M-MICRO - Festo 526305

Item no. FES-526305

Manufacturer Festo

EAN 4052568084042

Festo air-preparation unit for clean, regulated compressed air that protects downstream components.

TECHNICAL DATA

Betriebsdruck max [bar]	10.000000
HS-Code	84213925
Pneumatischer Anschluss	QS-4
Weight	0.064 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo air-preparation unit for clean, regulated compressed air that protects downstream components. The key technical data of this genuine Festo article are listed below.

size	Micro
Model series	D
installation position	vertical $\pm 5^\circ$
Filter porosity [μm]	5
Condensate drain	Manually rotating
Construction set up	Sintered filter with centrifugal separator
Max. condensate amount [ml]	3
Operating pressure [bar]	0 to 10
Normal nominal flow [l/min]	170
Operating medium	Inert gases Compressed air to ISO 8573-1:2010 [-:9:-]
Corrosion resistant class KBK	2 - moderate corrosion stress

Air purity class at the output	Compressed air to ISO 8573-1:2010 [6:8:4] Inert gases
Medium temperature [°C]	-10 to 60
ambient temperature [°C]	-10 to 60
Product weight [g]	64
Fastening type	pipe installation With Accessories Selectively:
Pneumatic connection 1	QS-4
Pneumatic connection 2	QS-4
Material information	RoHs compliant
Filter material	PE
Housing material	Aluminium die casting
Clamps material	PC