

Micro Filter LFMA-1/2-D-MAXI-A - Festo 186475

Item no. FES-186475

Manufacturer Festo

EAN 4052568146788

Festo air-preparation unit for clean, regulated compressed air that protects downstream components.

TECHNICAL DATA

Betriebsdruck max [bar]	12.000000
HS-Code	84213925
Pneumatischer Anschluss	G1/2
Weight	1.6 kg
Werkstoff	Zink-Druckguss



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo air-preparation unit for clean, regulated compressed air that protects downstream components. The key technical data of this genuine Festo article are listed below.

Model series	D
size	Maxi
Construction set up	Fibre filter
Filter porosity [µm]	0,01
Condensate drain	Fully automatic
Operating pressure [bar]	2 to 12
Operating medium	Compressed air to ISO 8573-1:2010 [6:8:4] Inert gases
Air purity class at the output	Compressed air to ISO 8573-1:2010 [1:7:2] Inert gases
Max. normal flow for air purity class [l/min]	1.500
Min. normal flow for air unit class [l/min]	500

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Filter effective degree [%]	99,9999
Clamp protection	Metal protection basket
Corrosion resistant class KBK	2 - moderate corrosion stress
Medium temperature [°C]	1.5 to 60
ambient temperature [°C]	-10 to 60
Residual oil content [mg/m ³]	0,01
Fastening type	pipe installation With Accessories Selectively:
installation position	vertical ± 5°
Pneumatic connection 1	G1/2
Pneumatic connection 2	G1/2
Housing material	Zinc pressure cast
Filter material	Borosilicate fibre
Clamps material	PC
Material information	Copper and PTFE-free RoHs compliant