

Fine Filter LFMB-D-MAXI-DA-A - Festo 532816

Item no. FES-532816


Manufacturer Festo

EAN 4052568165598

Festo air-preparation unit for clean, regulated compressed air that protects downstream components.

TECHNICAL DATA

Betriebsdruck max [bar]	12.000000
HS-Code	84213925
Weight	1.2 kg
Werkstoff	Zink-Druckguss



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo air-preparation unit for clean, regulated compressed air that protects downstream components. The key technical data of this genuine Festo article are listed below.

Model series	D
Construction set up	Fibre filter
Filter porosity [µm]	1
Condensate drain	Fully automatic
Operating pressure [bar]	2 to 12
Operating medium	Compressed air to ISO 8573-1:2010 [6:8:4] Inert gases
Air purity class at the output	Inert gases Compressed air to ISO 8573-1:2010 [5:7:3]
Filter effective degree [%]	99,99
Max. condensate amount [ml]	80
Clamp protection	Metal protection basket
Corrosion resistant class KBK	2 - moderate corrosion stress

Medium temperature [°C]	1.5 to 60
ambient temperature [°C]	-10 to 60
Bearing temperature [°C]	-10 to 60
Residual oil content [mg/m³]	0,5
Fastening type	pipe installation With Accessories Selectively:
installation position	vertical ± 5°
Pneumatic connection 1	Connection plate
Pneumatic connection 2	Connection plate
Housing material	Zinc pressure cast
Filter material	Borosilicate fibre
Clamps material	PC
Material information	Copper and PTFE-free RoHs compliant
Product weight [g]	1.021
Differential pressure indicator	Visual display