

Fine Filter LFMB-D-MIDI-A - Festo 192573

Item no. FES-192573

Manufacturer Festo

EAN 4052568014988

Festo air-preparation unit for clean, regulated compressed air that protects downstream components.

TECHNICAL DATA

Baugröße BG	Midi
Betriebsdruck max [bar]	12.000000
Corrosion resistance class CRC	2 - moderate corrosion stress
Design	Fibre filter
Filterfeinheit [µm]	1
HS-Code	84213925
Kondensatablass	fully automatic
Material	Die-cast zinc
Medium	Compressed air, neutral gases
Mounting position	vertical ± 5°
Operating conditions	ISO 8573-1
Series	LFMB
Temperature (max.)	60
Weight	0.7 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo air-preparation unit for clean, regulated compressed air that protects downstream components. The key technical data of this genuine Festo article are listed below.

Model series	D
size	Midi
Construction set up	Fibre filter
Filter porosity [µm]	1
Condensate drain	Fully automatic
Operating pressure [bar]	2 to 12
Operating medium	Compressed air to ISO 8573-1:2010 [6:8:4] Inert gases
Air purity class at the output	Inert gases Compressed air to ISO 8573-1:2010 [5:7:3]
Filter effective degree [%]	99,99
Max. condensate amount [ml]	43

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Clamp protection	Metal protection basket
Corrosion resistant class KBK	2 - moderate corrosion stress
Medium temperature [°C]	1.5 to 60
ambient temperature [°C]	-10 to 60
Bearing temperature [°C]	-10 to 60
Residual oil content [mg/m ³]	0,5
Fastening type	pipe installation With Accessories Selectively:
installation position	vertical ± 5°
Pneumatic connection 1	Connection plate
Pneumatic connection 2	Connection plate
Housing material	Zinc pressure cast
Filter material	Borosilicate fibre
Clamps material	PC
Material information	Copper and PTFE-free RoHs compliant