

Fine Filter Combinati LFMBA-1/4-D-MIDI-DA - Festo 532866

Item no. FES-532866

Manufacturer Festo

EAN 4052568166021

Festo air-preparation unit for clean, regulated compressed air that protects downstream components.

TECHNICAL DATA

Betriebsdruck max [bar]	16.000000
HS-Code	84213925
Pneumatischer Anschluss	G1/4
Weight	1.6 kg
Werkstoff	Zink-Druckguss



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo air-preparation unit for clean, regulated compressed air that protects downstream components. The key technical data of this genuine Festo article are listed below.

size	Midi
Model series	D
installation position	vertical $\pm 5^\circ$
Filter porosity [μm]	0,01
Filter effective degree [%]	99,9999
Condensate drain	Manually rotating
Construction set up	Fibre filter
Max. condensate amount [ml]	43
Clamp protection	Metal protection basket
Operating pressure [bar]	1 to 16
Operating medium	Compressed air to ISO 8573-1:2010 [6:8:4] Inert gases

Air purity class at the output	Compressed air to ISO 8573-1:2010 [1:7:2] Inert gases
Medium temperature [°C]	1.5 to 60
Residual oil content [mg/m³]	0,01
ambient temperature [°C]	-10 to 60
Product weight [g]	1.429
Fastening type	pipe installation With Accessories
Pneumatic connection 1	G1/4
Pneumatic connection 2	G1/4
Material information	Copper and PTFE-free RoHs compliant
Filter material	Borosilicate fibre
Housing material	Zinc pressure cast
Clamps material	PC