

Lubricator LOE-1/2-D-MIDI - Festo 159587

Item no. FES-159587

Manufacturer Festo

EAN 4052568011819

Festo air-preparation unit for clean, regulated compressed air that protects downstream components.

TECHNICAL DATA

Betriebsdruck max [bar]	16.000000
HS-Code	84248970
Pneumatischer Anschluss	G1/2
Weight	0.9 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo air-preparation unit for clean, regulated compressed air that protects downstream components. The key technical data of this genuine Festo article are listed below.

size	Midi
Model series	D
installation position	vertical $\pm 5^\circ$
Construction set up	Proportional standard oil mist lubricator
Max. oil filling volume [cm ³]	110,0
Clamp protection	Metal protection basket
Operating pressure [bar]	0 to 16
Minimum flow for oiler function [l/min]	8
Normal nominal flow [l/min]	6.100
Maritime classification	see Certificate
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4] Inert gases

Information about operating and control medium	Oiled operation not possible
Corrosion resistant class KBK	2 - moderate corrosion stress
Bearing temperature [°C]	-10 to 60
Air purity class at the output	Compressed air to ISO 8573-1:2010 [7:4:-] Inert gases
Medium temperature [°C]	-10 to 60
ambient temperature [°C]	-10 to 60
Product weight [g]	630
Fastening type	With Accessories
Pneumatic connection 1	G1/2
Pneumatic connection 2	G1/2
Material information	RoHs compliant
Clamps material	PC