

Pressure Regulator LR-1/8-D-7-O-MINI - Festo 162598

Item no. FES-162598

Manufacturer Festo

EAN 4052568072247

Festo valve for fast, reliable control of compressed-air direction and flow.

TECHNICAL DATA

Betriebsdruck max [bar]	16.000000
HS-Code	84811099
Pneumatischer Anschluss	G1/8
Weight	0.38 kg
Werkstoff	Zink-Druckguss



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

size	Mini
Model series	D
Actuation fuse	Rotary button with stopper
installation position	arbitrary
Construction set up	Directly controlled membrane control valve
Controller function	Output pressure constant With relieving With Pre-pressure compensation
pressure display	G1/8 prepared
Operating pressure [bar]	1 to 16
Pressure regulation range [bar]	0.5 to 7
Max. pressure hysteresis [bar]	0,2
Normal nominal flow [l/min]	1.000

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Maritime classification	see Certificate
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4] Inert gases
Information about operating and control medium	Oiled operation possible (required in further operations)
Air purity class at the output	Compressed air to ISO 8573-1:2010 [7:4:4] Inert gases
Medium temperature [°C]	-10 to 60
ambient temperature [°C]	-10 to 60
Product weight [g]	300
Fastening type	Front panel integration pipe installation With Accessories
Pneumatic connection 1	G1/8
Pneumatic connection 2	G1/8
Material information	Copper and PTFE-free RoHs compliant
Connection plate material	Zinc pressure cast
Seals material	NBR
Housing material	Zinc pressure cast