

Pressure Regulator LR-3/4-D-7-MAXI - Festo 162588

Item no.	FES-162588	Manufacturer	Festo
Manufacturer no.	LR-3/4-D-7-MAXI	EAN	4052568012533

Festo valve for fast, reliable control of compressed-air direction and flow.

TECHNICAL DATA

Article authenticity	Original product
Betriebsdruck max [bar]	16.000000
Condition of article	New
HS-Code	84811099
Pneumatischer Anschluss	G3/4
Weight	1.2 kg
Werkstoff	Zink-Druckguss



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

size	Maxi
Model series	D
Actuation fuse	Rotary button with stopper
installation position	arbitrary
Construction set up	Pre-controlled piston control valve
Controller function	Output pressure constant With relieving
pressure display	with pressure gauge
Operating pressure [bar]	0 to 16
Pressure regulation range [bar]	0.5 to 7
Max. pressure hysteresis [bar]	0,4

Normal nominal flow [l/min]	12.000
Maritime classification	see Certificate
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4] Inert gases
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	2 - moderate corrosion stress
Air purity class at the output	Compressed air to ISO 8573-1:2010 [7:4:4] Inert gases
Medium temperature [°C]	-10 to 60
ambient temperature [°C]	-10 to 60
Product weight [g]	1.200
Fastening type	Front panel integration pipe installation With Accessories
Pneumatic connection 1	G3/4
Pneumatic connection 2	G3/4
Material information	RoHs compliant
Connection plate material	Zinc pressure cast
Seals material	NBR
Housing material	Zinc pressure cast