

Differential Pressure LRL-3/8-QS-12 - Festo 153520

Item no. FES-153520

Manufacturer Festo

EAN 4052568070946

Festo pneumatic component for industrial automation and compressed-air applications in proven quality.

TECHNICAL DATA

Design	Directly controlled piston control valve, With Continuous pressure supply
HS-Code	84811099
Medium	Druckluft
Mounting position	arbitrary
Pneumatischer Anschluss	G3/8
Regelbereich max. [bar]	6
Serie	LRL
Temperature (max.)	60
Weight	0.08 kg
Werkstoff	PBT



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic component for industrial automation and compressed-air applications in proven quality. The key technical data of this genuine Festo article are listed below.

Controller function	Constant differential pressure With Return current behaviour
Pneumatic connection 1	G3/8
Pneumatic connection 2	QS-12
Fastening type	Screwable
Nominal flow open [l/min]	438
Pressure regulation range [bar]	2 to 6
Input pressure 1 [bar]	0 to 9
ambient temperature [°C]	0 to 60
Housing material	PBT reinforced
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-]
Actuation fuse	Knurled screw with locking

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

installation position	arbitrary
Construction set up	Directly controlled piston control valve With Continuous pressure supply
Nominal flow closed [l/min]	379
Information about operating and control medium	Oiled operation possible (required in further operations)
Product weight [g]	78,0
Stud material	brass nickel-plated
Material information	RoHs compliant
Thread sealing material	PTFE