

Differential Pressure LRL-1/8-QS-4 - Festo 153499

Item no. FES-153499

Manufacturer Festo

EAN 4052568070762

Festo pneumatic component for industrial automation and compressed-air applications in proven quality.

TECHNICAL DATA

HS-Code 84811099

Pneumatischer Anschluss G1/8

Weight 0.02 kg

Werkstoff PBT



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic component for industrial automation and compressed-air applications in proven quality. The key technical data of this genuine Festo article are listed below.

Controller function	Constant differential pressure With Return current behaviour
Pneumatic connection 1	G1/8
Pneumatic connection 2	QS-4
Fastening type	Screwable
Nominal flow open [l/min]	100
Pressure regulation range [bar]	2 to 6
Input pressure 1 [bar]	0 to 9
ambient temperature [°C]	0 to 60
Housing material	PBT reinforced
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-]
Actuation fuse	Knurled screw with locking

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

installation position	arbitrary
Construction set up	Directly controlled piston control valve With Continuous pressure supply
Nominal flow closed [l/min]	96
Information about operating and control medium	Oiled operation possible (required in further operations)
Product weight [g]	19,0
Stud material	brass nickel-plated
Material information	RoHs compliant
Thread sealing material	PTFE