

Lubricator MS12-LOE-G-U - Festo 537156

Item no. FES-537156

Manufacturer Festo

EAN 4052568172312

Festo air-preparation unit for clean, regulated compressed air that protects downstream components.

TECHNICAL DATA

Betriebsdruck max [bar]	16.000000
Corrosion resistance class CRC	2 - moderate corrosion stress
Design	Proportional standard oil mist lubricator
Dichtmaterial	NBR
Durchfluss [l/min]	2000022000
HS-Code	84248970
Material	Aluminium
Medium	Air
Mounting position	vertical $\pm 5^\circ$
Operating conditions	ISO 8573-1
Series	MS12
Temperature (max.)	60
Weight	8 kg



STANDARDS & COMPLIANCE

DIN ISO 8573-1

DESCRIPTION

Festo air-preparation unit for clean, regulated compressed air that protects downstream components. The key technical data of this genuine Festo article are listed below.

size	12
Model series	MS
installation position	vertical $\pm 5^\circ$
Construction set up	Proportional standard oil mist lubricator
Max. oil filling volume [cm ³]	1.500
Clamp protection	Integrated as metal bowl
Operating pressure [bar]	1 to 16
Minimum flow for oiler function [l/min]	400
Normal nominal flow [l/min]	20000 to 22000
Operating medium	Air quality class 5:7 acc. to DIN ISO 8573-1

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Corrosion resistant class KBK	2 - moderate corrosion stress
Bearing temperature [°C]	-10 to 60
Medium temperature [°C]	0 to 60
Oil viscosity	ISO VG 32
ambient temperature [°C]	0 to 60
Product weight [g]	6.500
Fastening type	pipe installation With mounting bracket Selectively:
Pneumatic connection 1	Internal
Pneumatic connection 2	Internal
Cover material	PA
Seals material	NBR
Housing material	Aluminium die casting
Clamps material	Aluminium wrought alloy