

Filter MS6-LF-1/2-EUV - Festo 529621

Item no. FES-529621

Manufacturer Festo

EAN 4052568164089

Festo air-preparation unit for clean, regulated compressed air that protects downstream components.

TECHNICAL DATA

Betriebsdruck max [bar]	12.000000
HS-Code	84213925
Pneumatischer Anschluss	G1/2
Weight	0.95 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo air-preparation unit for clean, regulated compressed air that protects downstream components. The key technical data of this genuine Festo article are listed below.

size	6
Model series	MS
installation position	vertical $\pm 5^\circ$
Filter porosity [μm]	40
Condensate drain	Fully automatic
Construction set up	Sintered filter with centrifugal separator
Max. condensate amount [ml]	38
Clamp protection	Integrated as metal bowl
Operating pressure [bar]	2 to 12
Normal nominal flow [l/min]	4.100
Operating medium	Inert gases Compressed air to ISO 8573-1:2010 [7:9:-]

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Corrosion resistant class KBK	2 - moderate corrosion stress
Bearing temperature [°C]	-10 to 60
Food compatibility	See expanded material information
Air purity class at the output	Compressed air to ISO 8573-1:2010 [7:8:4]
Medium temperature [°C]	5 to 60
ambient temperature [°C]	5 to 60
Product weight [g]	820
Fastening type	pipe installation With Accessories Selectively:
Pneumatic connection 1	G1/2
Pneumatic connection 2	G1/2
Material information	Copper and PTFE-free RoHs compliant
Seals material	NBR
Filter material	PE
Housing material	Aluminium die casting
Clamps material	Aluminium wrought alloy
Dividing plate material	POM