

Lubricator MS6-LOE-1/2-R - Festo 529775

Item no. FES-529775

Manufacturer Festo

EAN 4052568085414

Festo air-preparation unit for clean, regulated compressed air that protects downstream components.

TECHNICAL DATA

Betriebsdruck max [bar]	16.000000
Corrosion resistance class CRC	2 - moderate corrosion stress
Design	Proportional standard oil mist lubricator
Durchfluss [l/min]	7200
HS-Code	84248970
Medium	Druckluft, neutrale Gase
Mounting position	vertical $\pm 5^\circ$
Pneumatischer Anschluss	G1/2
Serie	MS6
Temperature (max.)	60
Weight	0.7 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo air-preparation unit for clean, regulated compressed air that protects downstream components. The key technical data of this genuine Festo article are listed below.

size	6
Model series	MS
installation position	vertical $\pm 5^\circ$
Construction set up	Proportional standard oil mist lubricator
Max. oil filling volume [cm ³]	75
Clamp protection	Plastic basket
Operating pressure [bar]	1 to 16
Minimum flow for oiler function [l/min]	50
Normal nominal flow [l/min]	7.200
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4] Inert gases

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Information about operating and control medium	Oiled operation possible
Corrosion resistant class KBK	2 - moderate corrosion stress
Bearing temperature [°C]	-10 to 60
Food compatibility	See expanded material information
Medium temperature [°C]	0 to 60
Oil viscosity	ISO VG 32
ambient temperature [°C]	0 to 60
Product weight [g]	600
Fastening type	pipe installation With Accessories Selectively:
Pneumatic connection 1	G1/2
Pneumatic connection 2	G1/2
Material information	RoHs compliant
Housing material	Aluminium die casting
Clamps material	PC