

Push-In T-Fitting QSTL-1/8-8-50 - Festo 130826

| | | | |
|-------------------------|---------------|---------------------|---------------|
| Item no. | FES-130826 | Manufacturer | Festo |
| Manufacturer no. | QSTL-1/8-8-50 | EAN | 4052568025465 |

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

TECHNICAL DATA

| | |
|-------------------------|-------------------------|
| Article authenticity | Original product |
| Condition of article | New |
| HS-Code | 74122000 |
| Pneumatischer Anschluss | R1/8 |
| Weight | 0.019 kg |
| Werkstoff | PBT |



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

| | |
|---|---------------------|
| size | Standard |
| Nominal width [mm] | 6,0 |
| Seal type on stud | coating |
| installation position | arbitrary |
| Packing size | 50 |
| Construction set up | Push-pull principle |
| Operating pressure complete temperature range [bar] | -0.95 to 6 |
| Temperature depending operating pressure [bar] | -0.95 to 14 |
| Maritime classification | see Certificate |

| | |
|--|--|
| Operating medium | Compressed air to ISO 8573-1:2010 [7:-:-] Water according to manufacturer declaration at www.festo.com |
| Information about operating and control medium | Oiled operation possible |
| Corrosion resistant class KBK | 1 - low corrosion stress |
| ambient temperature [°C] | -10 to 80 |
| Product weight [g] | 19,0 |
| Pneumatic connection 1 | Male thread R1/8 |
| Pneumatic connection 2 | For hose exterior diameter 8 mm |
| Sleeve colour | blue |
| Material information | RoHs compliant |
| Housing material | PBT |
| Sleeve material | POM |
| Tube seal, hose seal material | NBR |
| Hose clamping segment material | High-alloyed stainless steels |
| Number of outlets | 2 |
| Number of supply lines | 1 |