

Linear/Swivel Clamp CLR-63-50-R-P-A-K11-R8 - Festo 535508

Item no. FES-535508

Manufacturer Festo

EAN 4052568169190

Festo rotary actuator for defined swivel motion and positioning in automation.

TECHNICAL DATA

Ausführungstyp	Schweißspritzerschutz, Staubschutz
Betriebsdruck max [bar]	10.000000
Bore (mm)	63.000000
Corrosion resistance class CRC	2 - moderate corrosion stress
Cushioning	P: Elastic silencer rings / plates double-sided
Design	Piston, piston rod, cylinder tube
Dichtmaterial	NBR, TPE-U(PU)
Funktion	double-acting
HS-Code	84123100
Material	Aluminium
Medium	Compressed air
Mounting position	arbitrary
Operating conditions	ISO 8573-1
Pneumatic connection	G1/8
Position sensing	Yes
Series	CLR
Temperature (max.)	80
Weight	2.6 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo rotary actuator for defined swivel motion and positioning in automation. The key technical data of this genuine Festo article are listed below.

Total stroke [mm]	73
Piston diameter	63 mm
Piston rod thread	M10
Swivel angle	90 deg ± 2 deg
Clamping stroke [mm]	50
Dampening	P: Elastic silencer rings / plates double-sided

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

installation position	arbitrary
Construction set up	Piston piston rod cylinder tube
Position detection	For proximity switch
Swivel direction	Right
Operating pressure [bar]	2 to 10
Principle of operation	double acting
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	2 - moderate corrosion stress
ambient temperature [°C]	-10 to 80
Effective clamping strength at 2 bar [N]	441
Effective clamping strength at 4 bar [N]	823
Effective clamping strength at 6 bar [N]	1.386
Max. tightening torque Clamping finger screw [Nm]	47,0
Theoretical clamping strength at 6 bar [N]	1.682
Product weight [g]	2.625
Fastening type	With throughway bores With female thread With Accessories Selectively:
Pneumatic connection	G1/8
Flush screw material	Steel zinc plating
Cover material	Aluminium wrought alloy Coated
Seals material	NBR TPE-U(PU)
Housing material	Aluminium wrought alloy Smooth anodised
Piston rod material	Coated High-alloyed stainless steels
Cylinder tube material	Aluminium wrought alloy Smooth anodised
Variants	dust protection Welding spatter protection
Wiper material	PPS