

Signal Converter SVE4-IS-R-HM8-2N-M8 - Festo 544221

Item no. FES-544221

Manufacturer Festo

EAN 4052568184032

Festo pneumatic component for industrial automation and compressed-air applications in proven quality.

TECHNICAL DATA

HS-Code	85365019
Schutzart	IP65
Weight	0.065 kg



STANDARDS & COMPLIANCE

EN 60947-5-2

DESCRIPTION

Festo pneumatic component for industrial automation and compressed-air applications in proven quality. The key technical data of this genuine Festo article are listed below.

Permission	RCM mark UL us - Listed (OL)
UL - ambient temperature [°C]	-20 to 60
CE certificate (see declaration of conformity)	to EU EMC directive
Material information	Copper and PTFE-free
Signal range	0 - 20 mA ±0,6 mA
ambient temperature [°C]	-20 to 70
Control output	2xNPN
Switch function	Freely programmable
Switching element function	Switchable
Short circuit resistance	Cycling
Overload resistant	Available

Operating voltage range DC [V]	10 to 30
Electrical connection: input	M8x1 4 pin socket / container / acc. to EN 60947-5-2
Electrical connection: outlet	M8x1 4 pin acc. to EN 60947-5-2 Plug
Product weight [g]	19
Housing material	ABS
Setting options	Teach-in
Protection category	IP65
Corrosion resistant class KBK	2 - moderate corrosion stress