

On-Off Valve MS12-EM-G - Festo

541495

Item no. FES-541495

Manufacturer Festo

EAN 4052568179670

Festo valve for fast, reliable control of compressed-air direction and flow.

TECHNICAL DATA

Betriebsdruck max [bar]	20.000000
HS-Code	84812090
Weight	4.8 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO8573-1:2010

DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

Construction set up	Piston pusher
Actuation type	Manually
Exhaust function	Cannot be throttled
Control type	Direct
Valve function	3/2 bistable
Operating pressure [bar]	0 to 20
Normal nominal flow [l/min]	25000 to 32000
Operating medium	Compressed air to ISO8573-1:2010 [-:-:-]
Corrosion resistant class KBK	2 - moderate corrosion stress
Material information	Copper and PTFE-free
Medium temperature [°C]	-10 to 60

ambient temperature [°C]	-10 to 60
Fastening type	pipe installation With Accessories Selectively:
installation position	arbitrary
Flow direction	Not reversible
Product weight [g]	3.900
Pneumatic connection 1	Battery module
Pneumatic connection 2	Battery module
Pneumatic connection 3	G1
Control air supply	Internal
Seals material	NBR
Housing material	Aluminium die casting