

Mini Slide DGSL-20-200-P1A - Festo 544022

Item no. FES-544022

Manufacturer Festo

EAN 4052568183653

Festo pneumatic cylinder for precise linear motion and defined force in automation.

TECHNICAL DATA

Betriebsdruck max [bar]	8.000000
Bohrung (mm)	25.000000
HS-Code	84123100
Hub [mm]	200.000000
Pneumatischer Anschluss	G1/8
Weight	4.5 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic cylinder for precise linear motion and defined force in automation. The key technical data of this genuine Festo article are listed below.

Stroke [mm]	200
Alignable end position range / Length front [mm]	138,5
Alignable end position range / Length rear [mm]	49,5
Piston diameter	25 mm
Operating mode actuator unit	Joch
Dampening	P1: Elastic silencer rings / plates double-sided With fixed limit stop
installation position	arbitrary
Guide	Ball cage guide
Construction set up	Joch Kolben Kolbenstange Schlitten
Position detection	For proximity switch

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Operating pressure [bar]	1 to 8
Max. speed [m/s]	0,8
Repeatability	±0.01 mm
Principle of operation	double acting
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	0 - No corrosion stressing
ambient temperature [°C]	0 to 60
Impact energy at the end positions [J]	0,200
Dampening length [mm]	5,0
Max. force Fy [N]	4.600
Max. force Fz [N]	4.600
Max. torque Mx [Nm]	90
Max. torque My [Nm]	80,0
Max. torque Mz [Nm]	80,0
Theoretical force at 6 bar, Return flow [N]	247
Theoretical force at 6 bar, flow [N]	295
Moving mass [g]	1.807
Product weight [g]	4.402
Alternative connections	See product drawing
Fastening type	With throughway bores
Pneumatic connection	G1/8
Material information	Copper and PTFE-free RoHs compliant
Cover material	Aluminium wrought alloy
Seals material	HNBR
Housing material	Aluminium wrought alloy
Piston rod material	High-alloyed stainless steels