

Activated Carbon Filt MS6-LFX-1/2-U-HF - Festo 552927

Item no. FES-552927

Manufacturer Festo

EAN 4052568194901

Festo air-preparation unit for clean, regulated compressed air that protects downstream components.

TECHNICAL DATA

Betriebsdruck max [bar]	20.000000
HS-Code	84213925
Pneumatischer Anschluss	G1/2
Weight	1.8 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo air-preparation unit for clean, regulated compressed air that protects downstream components. The key technical data of this genuine Festo article are listed below.

size	6
Model series	MS
installation position	vertical $\pm 5^\circ$
Construction set up	activated carbon filter
Clamp protection	Integrated as metal bowl
Operating pressure [bar]	0 to 20
Max. normal flow for air purity class [l/min]	2.500
Operating medium	Compressed air to ISO 8573-1:2010 [1:4:2] Inert gases
Corrosion resistant class KBK	2 - moderate corrosion stress
Bearing temperature [°C]	-10 to 60
Air purity class at the output	Compressed air acc. to ISO 8573-1:2010 [1:4:1]

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Medium temperature [°C]	5 to 30
Residual oil content [mg/m³]	0,003
ambient temperature [°C]	-10 to 60
Product weight [g]	1.500
Fastening type	pipe installation With Accessories Selectively:
Pneumatic connection 1	G1/2
Pneumatic connection 2	G1/2
Material information	Copper and PTFE-free RoHs compliant
Filter material	Activated carbon
Housing material	Aluminium die casting
Clamps material	Aluminium wrought alloy