


Solenoid Valve CPVSC1-M4H-J-H-Q3 - Festo 547358

Item no.	FES-547358	Manufacturer	Festo
Manufacturer no.	CPVSC1-M4H-J-H-Q3	EAN	4052568188481

Festo valve for fast, reliable control of compressed-air direction and flow.

TECHNICAL DATA

Article authenticity	Original product
Betriebsdruck max [bar]	7.000000
Condition of article	New
HS-Code	84812090
Schutzart	IP40
Weight	0.057 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO 8573-1:2010 EN 60068-2-6 EN 60068-2-27

DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

Valve function	5/2 bistable
Actuation type	Electrical
Valve size [mm]	10
Normal nominal flow [l/min]	170
Operating pressure [bar]	-0.9 to 7
Construction set up	Piston pusher
Protection category	IP40
Exhaust function	Cannot be throttled
Sealing principle	Soft
installation position	arbitrary
Hand assist actuation	tentative

Control type	pilot operated
Control air supply	external
Flow direction	Not reversible
Überdeckung	positive Überdeckung
Control pressure [bar]	3 to 7
Max. positive test impulse at 0 signal [μ s]	500
Max. negative test impulse for 1 signal [μ s]	400
Coil characteristic value	5 V DC: 1 W
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)
Oscillation strength	Transport use test with severity level 2 to FN 942017-4 and EN 60068-2-6
Shock resistance	Shock test with degree of severity 2 to FN 942017-5 and EN 60068-2-27
Corrosion resistant class KBK	1 - low corrosion stress
ambient temperature [$^{\circ}$ C]	-5 to 50
Product weight [g]	56,5
Electrical connection	2 pin Plug
Fastening type	With throughway bores
Exhaust control connection 82/84	Hunt group
Pneumatic connection 1	Hunt group
Pneumatic connection 2	QS-3
Pneumatic connection 3/5 combined	Hunt group
Pneumatic connection 4	QS-3
Material information	RoHs compliant
Seals material	NBR
Housing material	Aluminium die casting
Shifting time um [ms]	8
Medium temperature [$^{\circ}$ C]	-5 to 50
Permission	c UL us - Recognized (OL)