

Multi-Pin Plug Socket NECA-S1G9-P9-MP3 - Festo 552703

Item no. FES-552703

Manufacturer Festo

EAN 4052568095352

Festo pneumatic component for industrial automation and compressed-air applications in proven quality.

TECHNICAL DATA

Betriebsspannung	24 V DC
Corrosion resistance class CRC	2 - moderate corrosion stress
Dichtmaterial	NBR
HS-Code	85366990
Schutzart	IP65
Temperature (max.)	50
Weight	0.085 kg
Werkstoff	Polyamid (PA)



STANDARDS & COMPLIANCE

IEC 60529

DESCRIPTION

Festo pneumatic component for industrial automation and compressed-air applications in proven quality. The key technical data of this genuine Festo article are listed below.

Fastening type	With throughway bores
Product weight [g]	60
Electrical connection 1	Socket, Sub-D, 9 pin
Electrical connection 2	Screw clamp, 9 pin
Operating voltage range DC [V]	21.6 to 26.4
Nominal operating voltage DC [V]	24
Current carrying capacity at 40°C [A]	1
Permitted cable diameter [mm]	5 to 10
Connection cross-section [mm²]	0.34 to 1
Information about connection cross-section	0.34-0.5 mm² with wire end sleeves
Protection category	IP65 acc. to IEC 60529

ambient temperature [°C]	0 to 50
Bearing temperature [°C]	-20 to 70
Relative humidity	95 % Not condensing
Corrosion resistant class KBK	2 - moderate corrosion stress
Housing material	PA reinforced
Locking nut material	Brass
Screws material	Steel
Seals material	NBR