

Sub-Base VABS-S2-1S-G38-B-R3 - Festo 546104

Item no.	FES-546104	Manufacturer	Festo
Manufacturer no.	VABS-S2-1S-G38-B-R3	EAN	4052568092146

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

TECHNICAL DATA

Article authenticity	Original product
Betriebsdruck max [bar]	10.000000
Condition of article	New
HS-Code	84819000
Schutzart	IP65
Weight	0.386 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

Build.width [mm]	42
Based on standard	ISO 5599-2
installation position	arbitrary
Control air supply	Internal
Operating pressure [bar]	-0.9 to 10
Operating voltage range DC [V]	24
Surge voltage strength [kV]	0,8
Current carrying capacity at 40°C [A]	2
Degree of contamination	3
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]

Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	0 - No corrosion stressing
Protection category	IP65 NEMA 4 In mounted condition
ambient temperature [°C]	-5 to 50
Product weight [g]	386
Fastening type	With throughway bores
Material information	RoHs compliant
Connection plate material	Aluminium die casting