

Sub-Base VABS-S2-1S-N38-C1 - Festo 546761

Item no. FES-546761

Manufacturer Festo

EAN 4052568092498

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

TECHNICAL DATA

Betriebsdruck max [bar]	10.000000
HS-Code	84819000
Schutzart	IP65
Weight	0.371 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

Build.width [mm]	42
Based on standard	ISO 5599-2
installation position	arbitrary
Control air supply	external
Operating pressure [bar]	-0.9 to 10
Operating voltage range AC [V]	110
Operating voltage range DC [V]	24
Surge voltage strength [kV]	4,0
Current carrying capacity at 40°C [A]	2
Degree of contamination	3
CE certificate (see declaration of conformity)	to EU low voltage directive

Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	0 - No corrosion stressing
Protection category	IP65 NEMA 4 In mounted condition
ambient temperature [°C]	-5 to 50
Product weight [g]	371
Fastening type	With throughway bores
Material information	RoHs compliant
Connection plate material	Aluminium die casting
Connection cross-section [mm²]	0.08 to 0.75