

Push-In Fitting CRQS-1/8-6-I - Festo 132330

Item no. FES-132330

Manufacturer Festo

EAN 4052568027957

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

TECHNICAL DATA

HS-Code	73072910
Pneumatischer Anschluss	R1/8
Weight	0.0093 kg
Werkstoff	Edelstahl



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

size	Standard
Nominal width [mm]	4,1
installation position	arbitrary
Design	straight shape
Packing size	1
Construction set up	Push-pull principle
Operating pressure complete temperature range [bar]	-0.95 to 10
Maritime classification	see Certificate
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-] Water according to manufacturer declaration at www.festo.com
Information about operating and control medium	Oiled operation possible

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Corrosion resistant class KBK	4 - particularly severe corrosion stress
Food compatibility	See expanded material information
ambient temperature [°C]	-15 to 120
Product weight [g]	8,4
Usable pipelines	PFAN
Pneumatic connection 1	Male thread R1/8
Pneumatic connection 2	For hose exterior diameter 6 mm
Material information	RoHs compliant
Housing material	High-alloyed stainless steels
Sleeve material	High-alloyed stainless steels
Tube seal, hose seal material	FPM
Hose clamping segment material	High-alloyed stainless steels
Fastening type	Innensechskant SW4