

Solenoid Coil MD-2-110VAC-PA - Festo 549904

Item no. FES-549904

Manufacturer Festo

EAN 4052568051938

Festo valve for fast, reliable control of compressed-air direction and flow.

TECHNICAL DATA

HS-Code	85059029
Mounting position	arbitrary
Norm	EN 175301-803
Protection rating	IP65
Temperature (max.)	50
Weight	0.11 kg



STANDARDS & COMPLIANCE

DIN EN 175301-803

DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

installation position	arbitrary
Power-on time	100 %
Coil characteristic value	110 V AC: 50/60 Hz, pull-in power 14.5 VA, holding power 10.5 VA
Permitted voltage oscillations	± 10 %
Protection category	IP65
ambient temperature [°C]	-20 to 50
Product weight [g]	110
Electrical connection	acc. to DIN EN 175301-803
Fastening type	With Knurled nut
Winding material	Copper
Performance factor cos {phi}	0.7

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

CE certificate (see declaration of conformity)	to EU low voltage directive
Permitted frequency oscillations	$\pm 10 \%$
Solenoid material	Duroplast Copper Steel
Max. tightening torque screw connection [Nm]	0,5