

Push-In Fitting NPQM-D-G14F-Q10-P10 - Festo 558680

Item no. FES-558680

Manufacturer Festo

EAN 4052568054748

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

TECHNICAL DATA

HS-Code	74122000
Pneumatischer Anschluss	G1/4
Weight	0.024 kg
Werkstoff	Messing



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

size	Standard
Nominal width [mm]	9,0
Construction set up	Push-pull principle
Operating pressure complete temperature range [bar]	-0,95 to 16
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-]
Information about operating and control medium	Oiled operation possible
Corrosion resistant class KBK	1 - low corrosion stress
ambient temperature [°C]	-20 to 70
Product weight [g]	24,4
Pneumatic connection 1	G1/4
Pneumatic connection 2	For hose exterior diameter 10 mm

Material information	RoHs compliant
Housing material	Nickel-plated brass
Tube seal, hose seal material	NBR