

Push-In L-Fitting NPQM-L-G18-Q6-P10 - Festo 558709

Item no. FES-558709

Manufacturer Festo

EAN 4052568054786

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

TECHNICAL DATA

Baugröße BG	Standard
Corrosion resistance class CRC	1 - low corrosion stress
Design	Push-pull principle
HS-Code	74122000
Material	Brass
Medium	Compressed air
Nennweite DN [mm]	5
Operating conditions	ISO 8573-1
Pneumatic connection	G1/8
Series	NPQM
Temperature (max.)	70
Weight	0.019 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

size	Standard
Nominal width [mm]	5,0
Seal type on stud	gasket
Construction set up	Push-pull principle
Operating pressure complete temperature range [bar]	-0,95 to 16
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-]
Information about operating and control medium	Oiled operation possible
Corrosion resistant class KBK	1 - low corrosion stress
ambient temperature [°C]	-20 to 70
Nominal tightening torque [Nm]	6,0
Tolerance to nominal tightening torque	± 20 %

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Product weight [g]	18,5
Pneumatic connection 1	G1/8
Pneumatic connection 2	For hose exterior diameter 6 mm
Material information	RoHs compliant
Housing material	Nickel-plated brass
Tube seal, hose seal material	NBR