

Push-In Fitting NPQM-DK-M7-Q4-P10 - Festo 558659

Item no. FES-558659

Manufacturer Festo

EAN 4052568054557

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

TECHNICAL DATA

HS-Code	74122000
Pneumatischer Anschluss	M7
Weight	0.0051 kg
Werkstoff	Messing



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

size	Standard
Nominal width [mm]	3,0
Seal type on stud	gasket
Construction set up	Push-pull principle
Operating pressure complete temperature range [bar]	-0,95 to 16
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-]
Information about operating and control medium	Oiled operation possible
Corrosion resistant class KBK	1 - low corrosion stress
ambient temperature [°C]	-20 to 70
Nominal tightening torque [Nm]	3,0
Tolerance to nominal tightening torque	± 20 %

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Product weight [g]	5,0
Pneumatic connection 1	M7
Pneumatic connection 2	For hose exterior diameter 4 mm
Material information	RoHs compliant
Housing material	Nickel-plated brass
Tube seal, hose seal material	NBR