

Sealing Ring OK-3/8 - Festo 531773

Item no. FES-531773

Manufacturer Festo

EAN 4052568048075

Festo pneumatic component for industrial automation and compressed-air applications in proven quality.

TECHNICAL DATA

HS-Code 39269097

Weight 0.0005 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic component for industrial automation and compressed-air applications in proven quality. The key technical data of this genuine Festo article are listed below.

Based on standard	ISO 16030
Packing size	1
Operating pressure complete temperature range [bar]	-0.95 to 10
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	2 - moderate corrosion stress
ambient temperature [°C]	-10 to 60
Hand tightening at room temperature.	yes
Nominal tightening torque [Nm]	12,50
Tolerance to nominal tightening torque	± 20 %

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Product weight [g]	0,44
Material information	Copper and PTFE-free RoHs compliant