

Bellows Gripper DHEB-14-E-U-S-P - Festo 1320823

Item no. FES-1320823


Manufacturer Festo

EAN 4052568230432

Festo gripper for secure handling and positioning of workpieces in automated processes.

TECHNICAL DATA

Betriebsdruck max [bar]	8.000000
Corrosion resistance class CRC	2 - moderate corrosion stress
Design	Contact membrane, Force controlled movement cycle
Funktion	einfachwirkend
HS-Code	84798997
Medium	Druckluft
Mounting position	arbitrary
Pneumatischer Anschluss	M3
Serie	DHEB
Temperature (max.)	60
Weight	0.075 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo gripper for secure handling and positioning of workpieces in automated processes. The key technical data of this genuine Festo article are listed below.

size	14
Bellows stroke [mm]	7,0
Min. diameter to be gripped [mm]	15,0
Max. diameter to be gripped [mm]	19,5
installation position	arbitrary
Principle of operation	single action closed
Construction set up	Contact membrane Force controlled movement cycle
Guide	Base guide
Position detection	without
Operating pressure [bar]	5 to 8

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

reset pressure [bar]	< 1 bar
Max. working frequency gripper [Hz]	<= 4 Hz
Min. opening time a 6 bar [ms]	20
Min. closing time at 6 bar [ms]	40
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	2 - moderate corrosion stress
Food compatibility	See expanded material information
ambient temperature [°C]	5 to 60
Centre exchange interval for bellows [Mio SP]	1,0
Guideline payload [KGM]	0,15
Product weight [g]	20
Fastening type	With Male thread With locking nut Selectively:
Pneumatic connection	M3
Material information	LABS containing materials included RoHs compliant
Bellows material	VMQ (Silicone)
Housing material	aluminium anodized