

Standards-Based Cyli DSBC-80-80-PPVA-N3 - Festo 1383336

Item no. FES-1383336

Manufacturer Festo

EAN 4052568016784

Festo pneumatic cylinder for precise linear motion and defined force in automation.

TECHNICAL DATA

Betriebsdruck max [bar]	12.000000
Bohrung (mm)	80.000000
HS-Code	84123100
Hub [mm]	80.000000
Pneumatischer Anschluss	G3/8
Weight	3.3 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic cylinder for precise linear motion and defined force in automation. The key technical data of this genuine Festo article are listed below.

Stroke [mm]	80
Piston diameter	80 mm
Piston rod thread	M20x1,5
Dampening	PPV: Pneumatic dampening both sides adjustable
installation position	arbitrary
Complies to standard	ISO 15552
Piston rod end	Male thread
Construction set up	Piston piston rod profile tube
Position detection	For proximity switch
Variants	One-sided piston rod
Operating pressure [bar]	0.4 to 12
Principle of operation	double acting

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	2 - moderate corrosion stress
ambient temperature [°C]	-20 to 80
Impact energy at the end positions [J]	1,8
Dampening length [mm]	31
Theoretical force at 6 bar, Return flow [N]	2.721
Theoretical force at 6 bar, flow [N]	3.016
Moving mass at 0 mm stroke [g]	810
Weight supplement per 10 mm stroke [g]	92
Base weight at 0 mm stroke [g]	2.660
Supplement moved mass per 10 mm stroke [g]	39
Fastening type	With female thread With Accessories Selectively:
Pneumatic connection	G3/8
Material information	RoHs compliant
Cover material	Alu-Druckguss, beschichtet
Werkstoff Kolbendichtung	TPE-U(PU)
Piston material	Aluminium wrought alloy
Piston rod material	High-alloyed steel
Werkstoff Kolbenstangen-Dichtabstreifer	TPE-U(PU)
Werkstoff Pufferdichtung	TPE-U(PU)
Werkstoff Pufferkolben	POM
Cylinder tube material	Aluminium-Knetlegierung, gleiteloxiert
Nut material	Zinc plated steel
Bearing material	POM
Flush screw material	Zinc plated steel