


Compact Cylinder ADNGF-50-40-PPS-A - Festo 574045

Item no.	FES-574045	Manufacturer	Festo
Manufacturer no.	ADNGF-50-40-PPS-A	EAN	4052568221683

Festo pneumatic cylinder for precise linear motion and defined force in automation.

TECHNICAL DATA



Article authenticity	Original product
Betriebsdruck max [bar]	10.000000
Bohrung (mm)	50.000000
Condition of article	New
HS-Code	84123100
Hub [mm]	40.000000
Pneumatischer Anschluss	G1/8
Weight	0.687 kg

STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic cylinder for precise linear motion and defined force in automation. The key technical data of this genuine Festo article are listed below.

Stroke [mm]	40
Piston diameter	50 mm
Based on standard	ISO 21287
Dampening	PPS: Self-setting pneumatic end position dampening
installation position	arbitrary
Construction set up	Piston piston rod profile tube
Position detection	For proximity switch
Anti-twist lock / guide	Guide rod with yoke

Operating pressure [bar]	1.4 to 10
Principle of operation	double acting
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	2 - moderate corrosion stress
ambient temperature [°C]	-20 to 80
Impact energy at the end positions [J]	2,80
Theoretical force at 6 bar, Return flow [N]	1.057
Theoretical force at 6 bar, flow [N]	1.178
Moving mass at 0 mm stroke [g]	287
Weight supplement per 10 mm stroke [g]	64
Base weight at 0 mm stroke [g]	687
Supplement moved mass per 10 mm stroke [g]	29
Pneumatic connection	G1/8
Material information	RoHs compliant
Cover material	aluminium anodized
Seals material	TPE-U(PUR)
Piston rod material	High-alloyed steel
Cylinder tube material	Aluminium wrought alloy Smooth anodised
Dampening length [mm]	6,0