

Hinge Cylinder DWB-63-100-Y-A-G - Festo 565758

Item no. FES-565758


Manufacturer Festo

EAN 4052568213015

Festo pneumatic cylinder for precise linear motion and defined force in automation.

TECHNICAL DATA

Betriebsdruck max [bar]	10.000000
Bohrung (mm)	63.000000
HS-Code	84123100
Hub [mm]	100.000000
Pneumatischer Anschluss	G1/4
Weight	1.9 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic cylinder for precise linear motion and defined force in automation. The key technical data of this genuine Festo article are listed below.

Stroke [mm]	100
Piston diameter	63 mm
Piston rod thread	M16x1,5
Abstand Gabelkopf zur Schwenkbefestigung [mm]	19,5
Dampening	PPV: Pneumatic dampening both sides adjustable
installation position	arbitrary
Construction set up	Kolben Zylinderrohr Kolbenstange mit Gabelkopf Schwenkbefestigung am Lagerdeckel
Geschwindigkeitsregelung	integrierte Drosseln beidseitig
Position detection	For proximity switch
Piston rod end	Außengewinde mit Gabelkopf

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Operating pressure [bar]	1 to 10
Principle of operation	double acting
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	0 - No corrosion stressing
ambient temperature [°C]	-10 to 60
Impact energy at the end positions [J]	1,3
Dampening length [mm]	20
Theoretical force at 6 bar, Return flow [N]	1.682
Theoretical force at 6 bar, flow [N]	1.870
Moving mass at 0 mm stroke [g]	741
Weight supplement per 10 mm stroke [g]	42
Base weight at 0 mm stroke [g]	1.600
Supplement moved mass per 10 mm stroke [g]	25
Alternative connections	See product drawing
Fastening type	mit Zubehör mit Schwenkbefestigung am Lagerdeckel
Pneumatic connection	G1/4
Werkstoff Gabelkopf	Vergütungsstahl Stahlguss
Material information	RoHs compliant
Wiper material	Bronze
Cover material	Aluminium die casting anodized
Seals material	NBR
Piston rod material	Quenched and tempered steel hard chromium plated
Cylinder tube material	Aluminium wrought alloy anodized