

Micro Filter MS9-LFM-G-AUV-HF - Festo 564053

Item no. FES-564053

Manufacturer Festo

EAN 4052568211356

Festo air-preparation unit for clean, regulated compressed air that protects downstream components.

TECHNICAL DATA

Betriebsdruck max [bar]	12.000000
Corrosion resistance class CRC	2 - moderate corrosion stress
Design	Fibre filter
Dichtmaterial	NBR
Filterfeinheit [µm]	0,01
HS-Code	84213925
Kondensatablass	manuell tastend
Medium	Druckluft
Mounting position	vertical ± 5°
Serie	MS9
Temperature (max.)	60
Weight	3.7 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo air-preparation unit for clean, regulated compressed air that protects downstream components. The key technical data of this genuine Festo article are listed below.

Model series	MS
size	9
Construction set up	Fibre filter
Filter porosity [µm]	0,01
Condensate drain	Manually cycling Fully automatic
Operating pressure [bar]	2 to 12
Operating medium	Compressed air to ISO 8573-1:2010 [6:8:4]
Air purity class at the output	Compressed air to ISO 8573-1:2010 [1:7:2]
Max. normal flow for air purity class [l/min]	7.800
Min. normal flow for air unit class [l/min]	390

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Filter effective degree [%]	99,9999
Max. condensate amount [ml]	225
Corrosion resistant class KBK	2 - moderate corrosion stress
Medium temperature [°C]	5 to 60
ambient temperature [°C]	5 to 60
Bearing temperature [°C]	-10 to 60
Residual oil content [mg/m³]	0,01
Fastening type	pipe installation With Accessories Selectively:
installation position	vertical ± 5°
Pneumatic connection 1	Battery module
Pneumatic connection 2	Battery module
Housing material	Aluminium die casting
Cover material	PA
Filter material	Borosilicate fibre
Clamps material	Aluminium wrought alloy
Window material	PA
Seals material	NBR
Product weight [g]	2.500